

HUNT *Simplicity*[®] FD Series Modular Dimming Systems for use with 0-10 Volt D. C. Architectural Dimming Ballasts 120 and 277Volt



FD-010-120



FD-010-277

Features:

- Continuous, flicker-free dimming to 5%
- Manually operates 1, 2 and 3 lamp compatible 0-10 Volt D.C. ballasts for T8, CFL and T5 lamps
- Remotely mounted single-gang control model PS-IFC-010
- Maximum load: 120V: 25 amps
277V: 11 amps
- Limited one-year warranty
- UL Listed.

Specifications:

- For use with approved 0-10 Volt D.C. dimming ballasts (see below)
- Wall-mounted, convection-cooled
- Requires remote control switch model PS-IFC-010 (single pole) or PS-IFC-3W-010 (3-way)
- Electronically circuited to withstand current and inverse voltage surges; include heavy-duty contactors

Approved ballasts:

Manufacturer	Name	Model
Advance Transformer	<i>Mark 7</i>	RZT(120V), VZT(277V) or IZT(dual) Series
Osram Sylvania/Motorola	<i>Quicktronic</i>	DIM Series
ESI/Universal	<i>SuperDim</i>	DIM-10 or DIM-D Series
MagneTek/Universal	<i>Ballastar</i>	B Series
Prescolite	<i>Intelectplus</i>	# must contain "D"
(Additional ballasts may also be compatible with this dimmer. Call HUNT to verify compatibility.)		

Dimensions: 10"H x 8 1/2 "W x 3 3/4 "D

Hunt Control Systems Inc.
200 Rome Court
Fort Collins CO 80524

Tel: (970) 484-9048
Fax: (970) 493-4125
huntdimming.com

Dimming.

It's all we do.
Since 1960.

**HUNT *Simplicity*[®] PS-IFC-010 Series Controls
for *FD-010* Series Modular Systems
for use with
Compatible 0-10 VDC Dimming Ballasts
120V and 277V**

Hunt Control Systems Inc.
200 Rome Court
Fort Collins CO 80524



PS-IFC-010
PS-IFC-010-3W

Tel: (970) 484-9048
Fax: (970) 493-4125
huntedimming.com

Features:

- Preset slide control – strap mount.
- Easy-to-operate, smooth-sliding linear control and switch.
- Available in single-pole or 3-way.
- Uses standard designer-style faceplate, included in box.
- Fits in any standard 2" deep single gang switchbox.
- Limited one-year warranty.
- Available in Ivory, White (standard colors), Brown, Black or Gray (custom colors).
- Rated for 120/277V applications.

Note:


All 3-way controls require a standard 3-way toggle switch to complete the circuit

Dimming.

It's all we do.
Since 1960.

**Typical Wiring Diagram
for HUNT *Simplicity*[®]
FD-010 and PS-IFC-010
120V and 277V
Single Pole**

Single Pole Wiring



POLARITY MUST BE MAINTAINED FOR PROPER OPERATION

Hunt Control Systems, Inc.

200 Rome Court
Fort Collins, CO 80524
U.S.A.


Ph: (970) 484-9048

Fax: (970) 493-4125

www.hunt dimming.com

**Typical Wiring Diagram
for
FD-010 and PS-IFC-010
120V and 277V
3-way**

3-way Wiring



POLARITY MUST BE MAINTAINED FOR PROPER OPERATION

HUNT Control Systems, Inc.

200 Rome Court
Fort Collins, CO 80524
U.S.A.

Ph: (970) 484-9048

Fax: (970) 493-4125

www.hunt dimming.com